

CERTIFICATION OF COMPLIANCE

Contains: WG1032BHF2 Description: 12"x 12" Suction Outlet Cover

Ratings: Are Shown in the Table Below.

Open Area: 41.07 sq-in

Certified to Comply with Section 1404 of the Virginia Graeme Baker Act (VGB) Pool & Spa Safety Act codified at 16 CFR part 1450. Initial Certification May 2011.

Manufactured: After November 1, 2020, by Division of Hayward Industries, Inc. at K4-A, 214028 Block K4- A, Export Processing Zone Wuxi New District Jiangsu Province PRC 214028, China.

Certified by Hayward Industries Inc. 400 Connell Drive, Suite 6100, Berkeley Heights, NJ 07922, Phone 908-355-7995 Contact at www.hayward-pool.com

Record Custodian is Customer Service at www.hayward-pool.com.

Email: <https://www.hayward-pool.com/shop/en/pools/contactForm>

Hayward Pool Products P.O. Box 5100 Clemmons, NC 27012-5100, Phone: 908-355-7995

To our customers, the Serial Number is a 17 digit number, preceded by letters "SN"

The Serial# Code: 21121005456789001


- First 2 digits are "21", conforming to UCC-128 symbology, signifying a serial #
- The 3rd – 4th digits are the manufacturing "plant" code (12 for Clemmons, 21 for Wuxi, China)
- The 5th – 8th are "year & month" of the date of manufacture and assembly
- The 9th – 17th are "unique serialized number" for each product

Tested to APSP 16 2017 per Section 1404 of the Virginia Graeme Baker Act (VGB) Pool & Spa Safety Act. Tested by IAPMO, 5001 E. Philadelphia Street, Ontario, CA 91761 (909)- 472-4100 in August 2020. Certificate at: http://pld.iapmo.org/file_info.asp?file_no=0006353

Date of Installation: _____

Suction outlet components have a finite life, the cover/grate should be inspected frequently and replaced at least every **7 years** or if found to be damaged, broken, cracked, missing, or not securely attached. All other components must be replaced at least every **28 years** or if found to be damaged, broken, or cracked. The screws must be replaced every time a cover is replaced.

Hayward Pool Products acknowledges that it is a federal crime to knowingly and willingly make materially false, fictitious, or fraudulent statements, representations, or omissions on this certification.



The Cover and Sump combination are rated at the following MAXIMUM ALLOWABLE FLOW RATES

WG1032BHF2	12" x 12"	GPM
3" Side Port Floor Mounted		416
4" Side Port Floor Mounted		484
3" Bottom Port Wall Mounted		308
4" Bottom Port Wall Mounted		308

Serial Number

▲ Warning – Suction Entrapment Hazard.

Suction in suction outlets and/or suction outlet covers which are installed in a small area and/or below the surrounding surface can cause severe injury or death due to body entrapment hazard.

To reduce the risk of body entrapment, installation of the field fabricated sumps must be such that the top of the mounted cover is a minimum of 1 1/2" above the finished pool surface over an area larger than 40" on a diagonal.